## Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application.

## Listing of Claims:

- An apparatus for transmitting a file through a network, the 1. (Currently amended)
- a file-splitting processor that for splitting[[s]] a file into a plurality of message segments apparatus comprising: and assigning one of a plurality of destination addresses to each segment, the plurality of message segments to a plurality of destination addresses being assigned to a receiving host; and

a message segment transmitter for transmitting the plurality of message segments to the receiving host using the plurality of destination addresses.

- The apparatus of claim 1 wherein the file-splitting processor further comprises a file converter that for convert[[s]]ing the file into N message segments such that enable reassembly of the file is reassemblable from a subset of any K of the message segments at the receiving host, wherein N and K are being positive integers[[,]] and N > K > 1.
- The apparatus of claim 1 wherein the file-splitting processor isconfigured for further assign[[s]]ing one of a plurality of source addresses to each of the plurality of message segments, thereby to imped[[e]]ing unauthorized attempts to observe ascertain the true source of [[a]] the transmitted file.
  - The apparatus of claim 1, further comprising a message segment monitor for detecting non-receipt of at least one of a second plurality of a subset of the plurality of message segments transmitted to the apparatus.
  - The apparatus of claim 1, further comprising an address allocator for assigning and reassigning N a subset of the plurality of destination addresses to the receiving host.

Amendment and Response U.S. Serial No. 10/025,017 Page 4 of 19

6. (Currently amended) An apparatus for transmitting a file through a network, the apparatus comprising:

a file-splitting processor that <u>for split[[s]]ting</u> the file into a plurality of message segments and assign[[s]]<u>ing one of</u> a plurality of source addresses to <u>each message segment of</u> the plurality of message segments, thereby to-disguis[[e]]<u>ing</u> the origin of the file; and

a message segment transmitter for transmitting the plurality of message segments to a receiving host.

- 7. (Currently amended) The apparatus of claim 6 wherein the file\_splitting processor is configured for further assigning one of a addresses the plurality of message segments to a plurality of destination addresses assigned to the receiving host to each message segment of the plurality of message segments.
- 8. (Currently amended) A method of <u>for</u> secure<u>ly</u> transmission<u>tting</u> of a file through a network, the method comprising:
  - (a) at a source host, splitting the file into a plurality of message segments;
- (b) addressing, at the source host, each message segment of the plurality of message segments to using one of a plurality of destination addresses assigned to a receiving host; and
- (c) transmitting the plurality of message segments to the receiving host with the plurality of destination addresses.
- 9. (Currently amended) The method of claim 8 wherein the plurality of message segments are addressed addressing comprises addressing the plurality of message segments in one-to-one correspondence to at least a portion subset of the plurality of destination addresses.
- 10. (Currently amended) The method claim 8 wherein splitting the file into a plurality of message segments comprises converting the file into N message segments such that enable reassembly of the file is reassemblable from a subset of any K of the message segments, where N and K are being positive integers[,] and N > K > 1.

Amendment and Response U.S. Serial No. 10/025,017 Page 5 of 19

- The method of claim 10, further comprising [[(d)]] assigning N 11. (Currently amended) destination addresses to the receiving host, and wherein the step of addressing comprises addressing the N message segments are addressed using one of to the N destination addresses assigned to the receiving host.
- The method of claim 11, further comprising causing the receiving host to cease receiving messages via on at least one of the N destination addresses in response to upon detection of an attack on the at least one of the destination addresses.
- The method of claim 12 wherein the receiving host is permitted to 13. (Currently amended) ceases to receive ing messages via no more than (N-K) destination addresses, thereby ensuring facilitating reassembly of the file by the host.
- The method of claim 11, further comprising: 14. (Currently amended)
  - (e) reassembling the N message segments into a reassembled file at the receiving host;
- (f) eausing the receiving host to splitting [[a]] the reassembled file into a second set of N message segments at the receiving host; and
- (f)(g) causing the receiving host to transmitting the second set of N message segments from the receiving host using the N destination addresses.
- The method of claim 8, further comprising: 15. (Currently amended)
- (d) eausing the receiving host to retransmitting the plurality of message segments from the receiving host.
- The method of claim 15 wherein retransmitting the plurality of 16. (Currently Amended) message segments from the receiving host the step of causing the receiving host to retransmit comprises eausing the receiving host to retransmitting the plurality of message segments to at least two of a plurality of intermediate hosts, to thereby relaying the plurality of message segments along more than one path through the network.

Amendment and Response U.S. Serial No. 10/025,017 Page 6 of 19

- 17. (Currently amended) The method of claim 8, further comprising:
- (d) selecting as a virtual network <u>comprising</u> a plurality of hosts, the plurality of hosts that includinges the receiving host; and
- (e) assigning each one host of the plurality of hosts to one a domain of a plurality of domains; [[, and]]
- (f) designating sets of the host pairs, each host pair comprising two hosts assigned to the same domain or a neighboring domain; and
- (g) wherein the step of transmitting comprises permitting constraining travel of each message segment one of the plurality of message segments to travel to the receiving host only via relays between host pairs, each one of the host pairs selected from one of a same domain and a neighboring domain.
- 18. (Currently amended) The method of claim 8, further comprising:
- (d) assigning <u>a source address selected from</u> a plurality of source addresses to <u>each</u> message segment of the plurality of message segments, thereby to imped[[e]]ing unauthorized attempts to observe a true ascertain the source of [[a]] the transmitted file.
- 19. (Currently amended) The method of claim 8, further comprising causing the receiving host to:
- (d) receiv[[e]]ing, at the receiving host, at least a portion of the plurality of message segments;
  - (e) reassembl[[e]]ing the file from the received message segments at the receiving host;
- (f) splitting the reassembled file into a second plurality of message segments at the receiving host; and
  - (g) transmitting the second plurality of message segments from the receiving host.

Amendment and Response U.S. Serial No. 10/025,017 Page 7 of 19

- 20. (Currently amended) The method of claim 8 wherein step (c) transmitting comprises transmitting the plurality of message segments to at least one of an intermediate host and a destination host.
- 21. (Currently amended) The method of claim 8 wherein step (c) transmitting comprises transmitting from at least one of a source host and an intermediate host.
- 22. (Currently amended) The method of claim 8, further comprising:
- (d) eausing the receiving host to-monitoring non-receipt by the receiving host of at least one of the plurality of message segments to detect tampering with message segment transmission.
- 23. (Currently amended) The method of claim 8, further comprising:
  - (d) allocating M destination addresses for assignment to the receiving host;
- (e) assigning N <u>destination</u> addresses <u>of the M allocated destination addresses</u>, <u>where N is</u> less than or equal to M; to the receiving host and
- (e) repeatedly changing periodically reassigning to the receiving host at least a portion of the N destination addresses.
- 24. (Currently amended) The method of claim 10, further comprising:
- (d) repeatedly changing periodically reassigning at least a portion subset of the plurality of destination addresses assigned to the receiving host while leaving at least K of the destination addresses unchanged thereby permitting continuous receipt of messages by the receiving host, and
- (e) notifying at least a portion of the network of the ehanged reassigned destination addresses, and wherein the step of addressing comprises addressing the plurality of message segments to at least the K unchanged addresses to permit continuous receipt of messages by the receiving host.

- The method of claim 8, further comprising: 25. (Currently amended)
- (d) eausing a sending host to adding status information associated with a sending host concerning itself to the message segment; and
- (e) eausing the receiving host to upon receipt by the receiving host, interpreting the status information to detect tampering with message segment transmission.
- The method of claim 8, further comprising: 26. (Currently amended)
  - (d) encoding the file to produce an encoded bit file having encoded bits, and
- (e) scrambling the encoded bits, and wherein the step of splitting the file splits such that the encoded bit file is split into a plurality of message segments.
- A method of securely transmitting ssion of a file through a 27. (Currently amended) network, the method comprising:
  - (a) splitting the file into a plurality of message segments at a source host;
- (b) at the source host, assigning one source address of a plurality of source addresses to each message segment of the plurality of message segments, thereby to-disguise[[e]]ing the origin of the file; and
  - (c) transmitting the plurality of message segments.
- The method of claim 27, further comprising: 28. (Currently amended)
- (d) assigning one destination address of a plurality of destination addressing the plurality of message segments to a plurality of addresses assigned to a receiving host to each message segment of the plurality of message segments.

Amendment and Response U.S. Serial No. 10/025,017 Page 9 of 19

- 29. (Currently amended) A method of for securely transmitting ssion of a message file through a network, the method comprising:
- (a) splitting the file into a plurality of message segments, each message segment comprising a destination specifier, <u>encrypted</u> protocol information, and <u>encrypted</u> message data; the protocol information and message data-being encrypted;
  - (b) eausing-receiving a message segment to be-received by at a receiving host;
- (c) eausing the receiving host to decrypting the message data routing information to determine a downstream destination host;
- (d) eausing the receiving host to encrypting the routing information and message data in accordance with an encryption protocol accessible to the destination host;
- (e), and to transmitting the [[thus-]]encrypted message segment to the destination host; and
- (e) (f) repeating steps (a)-(de) for other message segments, to thereby facilitat[[e]]ing recovery of the message by an ultimate the destination host.
- 30. (Currently amended) The method of claim 29 wherein the message segment has a length, and further comprising causing the receiving host to altering the length.
- 31. (Currently amended) The method of claim 29 further comprising causing wherein the receiving host to negotiate with and the destination host negotiate to determine the encryption protocol.
- 32. (Currently amended) The method of claim 29, further comprising causing the receiving host to adding status information concerning the receiving host itself to the message segment, and, eausing at the receiving host, to interpreting the status information to detect tampering with message segment transmission.

Amendment and Response U.S. Serial No. 10/025,017 Page 10 of 19

- A method of for defining and operating a network topology to 33. (Currently amended) camouflage network traffic patterns and volume, the network comprising a plurality of hosts, the method comprising:
- (a) assigning each one host of the a plurality of hosts to one a first domain of a plurality of domains; and
- (b) permitting restricting network traffic to message transmissions from each host to among hosts within the same domain of the host or a neighboring domains that neighbors the domain of the host, thereby defining multiple redundant relay paths among hosts, thereby; and (e) distributing traffic across the network, thereby camouflaging message sources and destinations.
- The method of claim 33, further comprising: 34. (Currently amended) (dc) reassigning at least one host of the plurality of the hosts to a second domain different one of the plurality of domains, thereby changing network traffic patterns.
- The method of claim 33, further comprising: 35. (Currently amended)
- (d) assigning [[a]] one of a plurality of addresses selected from a pool of addresses to with each one of the plurality of hosts;
- (e) reassigning at least one of the plurality of assigned addresses from [[a]] the pool of addresses; and
  - (f) notifying the plurality of hosts of the reassigned plurality of addresses.
- The method of claim 35 wherein the step of reassigning comprises 36. (Currently amended) reassigning only a portion of the plurality of addresses is reassigned at any one time to permit the use of a remaining unreassigned portion of the plurality of addresses addresses not having been reassigned while for notifying the plurality of hosts of the reassigned plurality of addresses.